## **NetBotz Smoke Detector – NBES0307**

### **Peformance Smoke Detection for Data Centers and Edge Networks**

The NetBotz Smoke Detector suppl ents building fire suppression systems to provides early detection of smoke in your data center or network closet, via customizable notifications sent from a NetBtoz appliance.

Compatible with all NetBotz appliances, the smoke detector cable is durable, and offers a number of intelligent features to simplify testing and maintenance.

When connected to a NetBotz 250, 450, or 570 rack monitoring appliance, or a NetBotz 355 or 455 wall monitroign appliance, the unitdetects the presence of smoke nearby, with a precision of 2.5 percent-obscuration-per-foot. The NetBotz appliance is then able to send a customizable alert via email, SMS, SNMP, or Modbus, depending on the model.

The Netbotz Smoke Detector can easily mount in an IT rack to be close to likely smoke and fire sources. It offers a reliable smoke detection solution that mitigates potential fire damage, costly business outages, and downtime.



#### Compatible With NetBotz Appliances



& NetBotz 450



NetBotz 250



NetBotz 355 & NetBotz 455

### **Features**

- Plug-in detector line
- Mounting kit designed for IT Rack installations included
- Wide-angle, dual-color LED indication
- Drift compensation and smoothing algorithms
- Loop testing
- UL listed and RoHS compliant

#### **Product SKUs**

NetBotz Smoke Detector NBES0307

# **Technical Specifications**

Operating Voltage Nominal: 12V

Maximum Ripple Voltage 30

Standby Current 50  $\mu$ A maximum average;

Maximum Alarm Current 20 mA

Detection Sensitivity Nominal: 2.5 percent-obscuration-per-foot

Operating Environment

Temperature 32° to 113°F (0° to 45°C)

Humidity 0% to 95% RH, non-condensing

Altitude 10,000ft (3000m) max.

Storage Environment 5° to 149°F (-15° to 65°C)

**Dimensions** 

Net Weight 1.54 lbs (.7 kg)

Maximum Height 5.2 inches (132 mm)

Maximum Width 6.89 inches (175 mm)

Maximum Depth 6.61 inches (168 mm)

Shipping Weight 2.16 lbs (0.98 kg)

Shipping Height 5.98 inches (152 mm)

Shipping Width 12.28 inches (312 mm)

Shipping Depth 8.5 inches (216 mm)

Certifications REACH: Contains No SVHCs; RoHS Compliant;

### **Compatible Appliances**

NetBotz 570 Rack Monitor

NetBotz 450 Rack Monitor

NetBotz 250 Rack Monitor

NetBotz 250 Rack Monitor

NetBotz 455 Wall Monitor

NetBotz 355 Wall Monitor

NBWL0355

Schneider Electric 800 Federal Street Andover, MA 01810 www.schneider-electric.com



