

# NetShelter Platform Quick SX/SV Comparisons

Feature	NetShelter SV	NetShelter SX	Notes
<b>Compatibility</b>			
InfraStruxure		<input checked="" type="checkbox"/>	SV – not optimized for row based infrastructure
Small IT Solution	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
<b>Convenience</b>			
Primarily toolless rack components		<input checked="" type="checkbox"/>	SV – Mounting rails, accessory brackets are non-toolless. full height side panels. Roof not removable.
<b>Agility</b>			
Adjustable mounting rails	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	SV – fasteners not captive, alignment feature different
Accessory mounting channel	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	SV – 4 brackets, install full-height accessories with no adjustment

<b>Feature</b>	<b>NetShelter SV</b>	<b>NetShelter SX</b>	<b>Notes</b>
<b>Casters</b>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	SX – low profile, SV – normal profile
<b>Roof eyebolt support</b>		<input checked="" type="checkbox"/>	
<b>Safety</b>			
<b>Shock packaging options for equipment shipment</b>		<input checked="" type="checkbox"/>	SV – no packaging options and not designed for equipment shipment
<b>Seismic rated</b>		<input checked="" type="checkbox"/>	SX – capable of IBC Zone 4 Seismic
<b>Load rating</b>	Static: 2205 lb (1000 kg) Dynamic: 1014 lb (460 kg)	Static: 3000 to 3750 lb Dynamic: 2250 lb (1022 kg)	
<b>UL Approved</b>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
<b>Heights</b>	42, 48U	24, 42, 45, 48U	
<b>Widths</b>	600, 800mm	600, 750mm (700 Japan Only)	

<b>Feature</b>	<b>NetShelter SX</b>	<b>NetShelter SV</b>
<b>Depths</b>	825, 1070, 1200mm	1060, 1200mm (1000mm China only)
<b>InfraStruxure Designer Integration</b>	Yes	No (SISD only)
<b>Roof</b>	Toolless removal, brushes	Fixed and structural, multiple cable entry openings
<b>Eyebolt support</b>	Yes	No
<b>Front /Rear door</b>	69% perforation pattern	69% perforation pattern
<b>Side panel</b>	Split half-height	Single full height
<b>Rear cable management</b>	Multiple channels, full height	4 accessory brackets
<b>Caster</b>	Low-profile	Normal-profile
<b>Joining bracket</b>	600mm & 24-in preinstalled	600mm preinstalled, 24-in hardware bag
<b>Cable brushes in roof</b>	Yes	800mm only

<b>Feature</b>	<b>NetShelter SX</b>	<b>NetShelter SV</b>
<b>Vertical mounting rail adjustability</b>	Easy full adjustability	Multiple adjustment points
<b>Shock packaging options</b>	Yes	No
<b>Seismic capabilities</b>	Yes	No
<b>UL Approved</b>	Yes	Yes